

FLOTATION IMPLEMENT TYRES



BLACKING TYRES



BT-FLT

Type Size	Pattern	Ply Rating	Rim Width (inch.)	Unloaded Inflation Dimension +/-2%		Free Rolling	Drive Rolling	I.P (Bar)
				CSW (mm)	OD (mm)	Load (kgs)	Load (kgs)	
400/55-22.5	BT-FI	16	11.75	407	1020	3550	2500	4
400/60-22.5	BT-FI	16	11.75	400	1070	4000	2800	3.5
385/65-22.5	BT-FI	18	11.75	407	1070	4500	3150	4.3
500/45-22.5	BT-FI	16	16	500	1015	3750	2650	3.6
500/60-22.5	BT-FI	16	16	500	1070	4875	3450	3.2
550/45-22.5	BT-FI	16	16	550	1070	4375	3075	2.8
550/50-22.5	BT-FI	12	16	550	1230	4500	3150	2.1
550/60-22.5	BT-FI	16	16	550	1230	5300	5300	3
600/50-22.5	BT-FI	16	20	600	1170	5150	3650	2.6
600/55-22.5	BT-FI	16	20	600	1230	5800	4000	2.6
700/40-22.5	BT-FI	16	24	700	1170	5300	3750	2.2
700/50-22.5	BT-FI	16	24	700	1270	5700	4750	2.4
600/56-26.5	BT-FI	12	20	600	1340	5150	3650	2
600/55-26.5	BT-FI	16	20	600	1340	6000	4375	2.6
700/50-26.5	BT-FI	12	24	700	1340	5800	4125	1.8
800/45-26.5	BT-FI	16	28	800	1340	7300	5000	2.2
650/65-30.35	BT-FI	12	20	650	1650	7750	5450	2.2
750/60-30.5	BT-FI	16	24	750	1650	8500	6000	2.2
850/50-30.5	BT-FI	16	28	850	1650	9500	6700	2.2

NOTE:

SIZE CUSTOMISATION IS AVAILABLE.

PLY RATING CUSTOMISATION IS AVAILABLE .

+91 844 840 1214 Whastapp & call

Email: export@blackingtyres.com Web.: www.blackingtyres.com