

AGRICULTURAL IMPLEMENT TYRES



BLACKING TYRES



Size	Ply Rating	Pattern	Rim Width	Unloaded Inflation Dimension +/-2%		Load Capacity (Kg)	I.P (Bar)
				CSW (mm)	OD (mm)		
5.90-15		BT-1					
6.70L-15SL	6	BT-1	4	170	710	730	3
7.60L-15SL	8	BT-1	7	193	722	950	3.4
7.50-16SL	8	BT-1	5.5	205	8.1	1060	3
9.5L-14SL	8	BT-1	7	240	735	1090	3
9.5L-15SL	8	BT-1	7	240	770	1120	3
10.0/80-12	10	BT-IMP	9	265	710	1285	3.9
10.0/75-15.3	10	BT-IMP/BT-R1	9	272	762	1950	4.5
10.0/75-15.3	12	BT-IMP/BT-R1	9	272	762	2180	5.25
11L-14SL	8	BT-1	8	265	750	1120	2.5
11L-15SL	8	BT-1	8	255	10	1150	2.5
11L-16SL	10	BT-1	8	270	10.6	1310	3
11.5/80-15.3	14	BT-IMP/BT-R1	9	295	846	2430	6.25
12.5L-15SL	10	BT-1	10	310	12.2	1550	3
12.5L-16SL	10	BT-1	10	310	12.2	1600	3
14L-16.1SL	12	BT-1	11	350	13.8	2120	3
16.5L-16.1SL	10	BT-1	14	425	16.7	2360	2.5
19.5L-16.1SL	12	BT-1	16	469	18.5	3000	2.5
21.5L-16.1SL	14	BT-1	18	553	21.8	3568	2.5
400/60-15.5	14	BT-IMP	13	400	875	2800	3.5

NOTE:

SIZE CUSTOMISATION IS AVAILABLE.

PLY RATING CUSTOMISATION IS AVAILABLE .

+91 844 840 1214 Whastapp & call

Email: export@blackingtyres.com

Web.: www.blackingtyres.com