

AGRICULTURAL TRACTOR FRONT TYRES



BLACKING TYRES



BT-F2



BT-GD



BT-J

Tyre Size	Ply Rating	Pattern	Rim width(inch)	Unloaded Inflation Dimension +/-2%		Static Loaded Radius (mm) +/-2%	Rolling Circumference +/-2.5% (mm)	Type	IP BAR	Max load(kgs)
				CSW (mm)	OD (mm)					
5.00-15	4	BTF2	4	142	659	307	1951	TT	2.8	365
6.50/8-12	6	BTR-1								
4.50-16	4	BTF2	3	124	657	311	1952	TT	3.1	365
5.00-16	6	BTF2	4	142	682	322	2025	TT	4.2	500
5.50-16	6	BT-GD, BT-J, BTF-2	4	156	722	340	2145	TT	3.7	525
6.00-16	8	BT-GD, BT-J, BTF-2	5.5	203	819	383	2220	TT	2.8	750
6.50-16	6	BT-J	4.5	182	767	359	2280	TT	3.1	615
7.50-16	8	BT-GD, BT-J, BTF-2	6	214	803	372	2393	TT	4.15	870
9.00-16	10	BTF2	8	239	857	398	2548	TT	3.9	1250
10.00-16	8	BTF-3	8	275	900	418	2682	TT	2.8	1215
11.00-16	8	BTF-3	10	320	970	448	2890	TT	2.5	1230
7.50-18	8	BTR-1	5.5	210	862	408	2650	TT	3.7	950
4.00-19	4	BTF2	3	117	717	343	2145	TT	2.4	355
6.00-19	6	BTF2	4.5	169	817	386	2445	TT	3.3	650
6.50-20	6	BT-J	4.5	177	867	409	2578	TT	3.1	730
7.50-20	8	BTF2	5.5	207	918	431	2745	TT	3.4	1030

NOTE:

SIZE CUSTOMISATION IS AVAILABLE.

PLY RATING CUSTOMISATION IS AVAILABLE .

+91 844 840 1214 Whastapp & call

Email: export@blackingtyres.com Web.: www.blackingtyres.com