

AGRICULTURAL TRACTOR REAR TYRES



BLACKING TYRES



BT-IRRIGATION



BT-R-1



BT-R-2



BT-R-2_

Type Size	Ply Rating	Pattern	Unloaded Inflation Dimension +/-2%			Rolling Circumference +/-2.5%	Static Loaded Radius (mm)	Type	Load Capacity Kg	IP Bar
			Rim Width(inch.)	CSM (mm)	OD (mm)					
7.50-16	8	BTR-1	6	214	803	2393	372	TT	1360	4.15
8.3-24	6	BTR-1	W7	211	995	3124		TT	825	2.4
9.5-24	8	BTR-1	W8	241	1050	3297		TT	1120	2.8
11.2-24	8	BTR-1	10	286	1102	3249	515	TT	1250	2.4
12.4-24	8	BTR-1	11	316	1158	3410	539	TT	1450	2.3
13.6-24	8	BTR-1	12	347	1212	3557	560	TT	1500	1.9
14.9-24	8	BT-IRRIGATION	13	378	1265	3719	583	TT	1800	1.8
14.9-24	8	BTR-1	13	379	1268	3719	583	TT	1800	1.8
15.5/80-24	14	BTR-1	13	394	1262	3965		TT	3150	3.5
16.0/70-20	14	BTR-1	14	418	1097	3444		TT	2650	3.5
16.9-24	8	BTR-1	15	431	1337	3925	613	TT	2060	1.7
14.9-26	8	BTR-1	13	378	1295	4066		TT	1750	1.6
18.4-26	12	BTR-1	16	467	1450	4550		TT	3000	2.3
11.2-28	8	BTR-1	10	284	1205	3543	565	TT	1320	2.4
12.4-28	8	BTR-1, BTR-2	11	318	1272	3748	598	TT	1550	2.3
13.6-28	8	BTR-1, BTR-2	12	345	1309	3851	610	TT	1650	2
14.9-28	8	BTR-1, BTR-2	13	378	1365	4013	634	TT	1880	1.8
16.9-28	10	BTR-1, BTR-2	15	432	1436	4220	649	TT	2430	2
16.9-30	8	BTR-1	15	432	1483	4366	688	TT	2300	1.7
18.4-30	12	BTR-1	16	469	1548	4557	716	TT	3250	2.3
16.9-34	8	BTR-1	15	431	1587	4660	738	TT	2130	1.7
18.4-34	10	BTR-1	16	469	1652	4851	766	TT	2415	1.5
11.2-38	8	BTR-1	W10s	288	1475	4630		TT	1450	1.6
13.6-38	10	BTR-1	12	345	1570	4930		TT	2240	2.5
15.5-38	10	BTR-1	14	397	1587	4660	746	TT	1840	1.9
16.9-38	8	BTR-1	15	431	1687	4954	788	TT	2240	1.7
18.4-38	8	BTR-1	16	469	1752	5145	816	TT	2430	1.4
18.4-38	12	BTR-1	16	469	1752	5145	816	TT	3250	2.2
23-1-26	16	BTR-1	20	587	1560	690	4545	TL	4375	2.3

NOTE:

SIZE CUSTOMISATION IS AVAILABLE.

PLY RATING CUSTOMISATION IS AVAILABLE .

+91 844 840 1214 Whastapp & call

Email: export@blackingtyres.com Web.: www.blackingtyres.com