

FORKLIFT/ SKIDSTEER/ MPT TYRES



BLACKING TYRES



BT-FKT



BT-MPT



BT-SS

Size	Ply rating	Pattern	Unloaded inflation dimension +/-2%			Load Capacity Kgs	I.P (Bar)
			Rim width(inch)	CSW(mm)	OD(mm)		
10-16.5	12	BT-SS	8.25	270	776	2375	6.2
12-16.5	12	BT-SS	9.75	312	825	2865	5.5
14-17.5	14	BT-SS	10.5	352	932	3875	5.5
15-19.5	14	BT-SS	11.75	389	1035	4560	4.8
10.5/80-18	10	BT-MTP	9	274	907	1550	5
12.5/80-18	12	BT-MTP	9	306	989	2650	4.7
Size	Ply Rating	Pattern	Unloaded inflation			Load Capacity Kgs	I.P (Bar)
			Rim width (inch)	CSW(mm)	OD (mm)		
5.00-8	8	BT-FL	3.00D / 3.25I	138	480	950	8.25
18x7-8	16	BT-FL	4.33R / 5 OF	175	474	1650	10
6.00-9	10	BT-FL	4.00E / 5 OF	172	552	1320	8.5
6.50-10	10	BT-FL	5.00F / 5.50F	187	607	1500	7.75
7.00-12	14	BT-FL	5.00S / 5.50F	192	672	2120	9
7.00-15	12	BT-FL	5.5/5	202	754	2360	8.25
7.50-15	14	BT-FL	6/5.5	222	787	2800	9.25
8.25-15	14	BT-FL	6.5/6	240	855	3250	8
28x9-15	14	BT-FL	6-Jul	220	720	2900	9
8.15-15	14	BT-FL	6-Jul	220	720	2900	9
300-15	18	BT-FL	8-Aug	300	840	4500	7.5
300-15	20	BT-FL	8-Aug	300	840	5000	10
12.00-20	16	BT-FL	8.5	315	1146	5540	6.6

NOTE:

SIZE CUSTOMISATION IS AVAILABLE.

PLY RATING CUSTOMISATION IS AVAILABLE .

+91 844 840 1214 Whastapp & call

Email: export@blackingtyres.com Web.: www.blackingtyres.com