

OFF THE ROAD (OTR) TYRES



BLACKING TYRES



BT-E3/L3



BT-G2/BT-L2



BT-R-4

Size	Ply Rating	Pattern	Rim Width (inch)	Unloaded Inflation Dimension +/-2%		Load Capacity Kgs	I.P (Bar)
				CSW (mm)	OD (mm)		
13.00-24	12	BTG-2	8	336	1282	2725	3
14.00-24	12	BTG-2	8	362	1348	3075	2.5
16.9-24	12	BTR-4	15	440	1310	3250	2.6
17.5L-24	12	BTR-4	15	445	1270	3450	2.7
19.5L-24	12	BTR-4	17	490	1325	3450	2.3
16.9-28	12	BTR-4	15	440	1410	3550	2.6
18.4-26	14	BTR-4	16	472	1425	4375	2.9
15.5-25	16	BTL-2	12	395	1275	2980	2.8
17.5-25	16	BTL-2	14	445	1350	3350	2.75
20.5-25	16	BTL-2	17	520	1490	4000	2.25
23.5-25	16	BTL-2	19.5	595	1615	5450	1.5
23.5-25	20	BTL-2	19.5	595	1615	6000	2
17.5-25	20	BT-E3/L3	14.00/1.5	450	1334	7300 @10KM/H	4.75
20.5-25	20	BT-E3/L3	17	520	1492	9500	4.5
23.5-25	20	BT-E3/L3	19.5	595	1617	10900	3.75
1600-25	32	BT-E3/L3	11.25/2.0	430	1490	12500	650
1800-25	32	BT-E3/L3	13.00/2.5	495	1615	15000	700

NOTE:

SIZE CUSTOMISATION IS AVAILABLE.

PLY RATING CUSTOMISATION IS AVAILABLE .

+91 844 840 1214 Whastapp & call

Email: export@blackingtyres.com Web.: www.blackingtyres.com