

THREE WHEELER TYRES



BLACKING TYRES



Size	Ply Rating	Pattern	Rim Width	Unloaded Inflation Dimension +/-2%		Load Capacity (Kg)	I.P (Bar)
				CSW (mm)	OD (mm)		
4.00-8	8	BT-RIB, BT-SR	3	415	110	400	4.25
4.00-10	6	BT-RIB	3	466	110	437	4.25
4.00-12	6	BT-SL	3	530	112	250	3.4
4.50-10	8	BT-LUG BT-SL	3.5	490	125	515	5
4.50-12	8	BT-RIB 2	3.5	529	122	257	2.1
5.00-10	8	BT-RIB BT-SL BT-LUG	3.5	516	134	580	5
5.00-12	8	BT-SL	3.5	516	134	590	5
5.20-14	6	BT-SL BT-LUG	3.5	612	132	375	2.1
5.50-13	6	BT-LUG	4	600	145	387	2.1
5.60-13	6	BT-LUG	4	600	145	387	2.1
5.65-12	6	BT-RIB	4	522	131	272	2.1
5.90-15	6	BT-RIB	4	668	150	462	2.1
155/80 D-12	8	BT-RIB BT-LUG	4.5	546	151	412	4.5
165/80 D-13	8	BT-LUG	4.5	597	165	670	4.5
165/80 D-14	8	BT-LUG	4.5	620	165	575	2.4

NOTE:

SIZE CUSTOMISATION IS AVAILABLE.

PLY RATING CUSTOMISATION IS AVAILABLE .

+91 844 840 1214 Whastapp & call

Email: export@blackingtyres.com Web.: www.blackingtyres.com